



Code: EI-35317
Date: 21 MAR 2000
Revised: 08 AUG 2011
Printed: 08 AUG 2011

WOLVERINE JOINING TECHNOLOGIES, LLC.

MATERIAL SAFETY DATA SHEET

Product: TIN/ANTIMONY (95/5) ORGANIC CORE SOLDER ALLOY, 35317

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Common Name : TIN/ANTIMONY (95/5) ORGANIC CORE SOLDER ALLOY
Chemical Name : CHEMICAL MIXTURE
Formula : CHEMICAL MIXTURE
Product CAS No.: CHEMICAL MIXTURE
Product Use : Welding/Brazing/Soldering

Supplier : WOLVERINE JOINING TECHNOLOGIES, LLC.
Address : 235 KILVERT STREET
City, St, Zip : WARWICK, RI 02886
Phone : 1-401-739-9550

FOR CHEMICAL EMERGENCY CALL CHEMTREC (24 HOURS):
1-800-424-9300 (US, Canada, Puerto Rico, Virgin Islands)
1-703-527-3887 (Outside Above Area)

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	CAS NO.	% Wt.
TIN	7440-31-5	93-95
ANTIMONY	7440-36-0	4-5
UREA	57-13-6	1-2.5
OXYALKYLENE POLYMER	25322-68-3	0.5-1.5

INGREDIENT NOTES

NOTE: The percentage by weight values reported for the ingredients in this product represent approximate formulation values. See Section 8 for Exposure Limits and Section 11 for Toxicological Information.

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Silver white metal with white powder core

Odorless

Flash Point: Not Applicable

Prolonged or repeated exposure may cause liver and kidney damage, and lung and cardiac disorders.

May cause eye, skin and respiratory tract irritation.

Harmful if swallowed. May cause irritation, abdominal pain, nausea, vomiting and diarrhea. Absorption may cause circulatory or respiratory failure.

Not a fire or explosion hazard in solid form. Finely divided dust may ignite and burn rapidly when mixed with air in the proper proportions. Toxic metal fumes may be released in a fire situation.

ROUTES OF ENTRY

Eyes? YES

Skin? YES

Inhalation? YES

Ingestion? YES

POTENTIAL HEALTH EFFECTS

EYE CONTACT may cause irritation.

SKIN CONTACT may cause irritation. Itchy rash and dermatitis are possible.

INHALATION may cause irritation of the respiratory tract with possible sore throat, coughing, labored breathing and dizziness. Short-term overexposure to fumes can cause a flu-like illness called metal fume fever. Symptoms include headache, sore throat, congestion, fever, chills, muscle aches, nausea, vomiting and weakness. Symptoms usually disappear within 24-48 hours. Severe overexposure can lead to pulmonary edema and death.

INGESTION is harmful. Symptoms include irritation, nausea, vomiting, abdominal pain and diarrhea. Absorption may cause systemic toxicity including liver and kidney damage, and circulatory or respiratory failure.

NOTE: The potential health effects described above only apply if dust or fume is formed.

CARCINOGENICITY

NTP? NO

IARC? NO

OSHA? NO

CHRONIC HEALTH HAZARDS

Prolonged overexposure to ANTIMONY may lead to liver and kidney damage, and lung and cardiac disorders.

Prolonged or repeated inhalation may cause a benign pneumoconiosis. Refer to Potential Health Effects.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

May adversely affect existing medical conditions, such as eye, skin, respiratory, liver and/or kidney ailments.

NOTE: See Section 8 for Exposure Limits, Section 11 for Toxicological Information and Section 12 for Ecological Information.

SECTION 4: FIRST AID MEASURES

EYE CONTACT: Immediately flush with plenty of water for at least 15 minutes. Hold eyelids open while flushing. If irritation persists, call a physician.

SKIN CONTACT: Immediately wash skin with soap and plenty of water. If irritation persists, call a physician.

INHALATION: If exposed to excessive levels of metal fumes, remove to fresh air and seek medical attention.

INGESTION: Get medical attention! If vomiting occurs, keep head lower than hips to prevent aspiration.

SECTION 5: FIRE-FIGHTING MEASURES

Flash Point: Not Applicable
Auto-Ignition: Not Applicable
LEL: Not Applicable
UEL: Not Applicable

NFPA HAZARD CLASSIFICATION

Health: 2 Flammable: 0 Reactivity: 0

HMIS HAZARD CLASSIFICATION

Health: 2* Flammable: 0 Reactivity: 0 Special: B

* Indicates the possibility of chronic health effects. See Chronic Health Hazards in Section 3 for more information.

EXTINGUISHING MEDIA

Use carbon dioxide, chemical foam or dry chemical. Use any means for extinguishing surrounding fire.

Do NOT use water on metal fires.

SPECIAL FIRE FIGHTING PROCEDURES

Wear NIOSH/MSHA approved positive-pressure self-contained breathing apparatus and protective clothing as specified in 29 CFR 1910.156.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Not a fire or explosion hazard in solid form. Finely divided dust may ignite and burn rapidly when mixed with air in the proper proportions. Toxic metal fumes may be released in a fire situation.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Contain spillage and scoop up or vacuum. Notification of the National Response Center (800/424-8802) may be required. Refer to EPA, DOT and applicable state and local regulations for current response information.

It is recommended that each user establish a spill prevention, control and countermeasure plan (SPCC). Such plan should include procedures applicable to proper storage, control and clean-up of spills, including reuse or disposal as appropriate (see Section 13: Disposal Considerations).

****NOTE**** In the event of an accidental release of this material, the above procedures should be followed. Additionally, proper exposure controls and personal protection equipment should be used (see Section 8: Exposure Control/Personal Protection), and disposal of the material should be in accordance with Section 13: Disposal Considerations.

SECTION 7: HANDLING AND STORAGE

Wash thoroughly after handling.

Store in a cool, dry location away from incompatible materials.

Avoid breathing any dust, mist or fumes resulting from the use of this product.

Avoid contact with any dusts, mists or fumes resulting from the use of this product.

Do not eat, drink, or smoke in work area.

Use only with adequate ventilation.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS

INGREDIENT	PEL-OSHA	TLV-ACGIH
TIN		
CAS NO.: 7440-31-5	2 mg/m ³	2 mg/m ³
ANTIMONY		
CAS NO.: 7440-36-0	0.5 mg/m ³	0.5 mg/m ³
UREA		
CAS NO.: 57-13-6	None Established	None Established
OXYALKYLENE POLYMER		
CAS NO.: 25322-68-3	None Established	None Established

NOTE: Both OSHA and the ACGIH list welding fumes as having an exposure limit of 5 mg/m³ (total particulate not otherwise classified). However, the ACGIH states that welding fumes must be tested frequently for individual components which are likely to be present to determine whether specific exposure limits are exceeded.

NOTE: The permissible exposure limits (PELs), threshold limit values (TLVs), potential health effects statements and SARA hazard categories may not be applicable as the hazardous ingredients listed are in the solid form. If dust, powder or fume is generated then these statements will be applicable.

Unless otherwise noted, all values are reported as 8-hour Time-Weighted Averages (TWAs) and total dust (particulates only). All ACGIH TLVs refer to the 1999 Standards. All OSHA PELs refer to 29 CFR Part 1910 Air Contaminants: Final Rule, January 19, 1989.

RESPIRATORY PROTECTION

If dust or fume is generated, a NIOSH/MSHA approved respirator may be necessary. Follow all requirements for respiratory programs and selection set forth in the OSHA regulations (29 CFR 1910.139).

VENTILATION

General; local exhaust ventilation as necessary to control any air contaminants to within their PELs or TLVs during the use of this product.

PROTECTIVE EQUIPMENT

Safety glasses (with side shields).
Body protection as necessary to prevent skin contact.
Refer to ANSI/ASC Z49.1-94 (Safety in Welding, Cutting and Allied Processes), published by the American Welding Society, for further information on the selection of personal protective equipment.

PERSONNEL SAMPLING PROCEDURE

For METALLIC COMPONENTS: Refer to NIOSH Manual of Analytical Methods (NMAM), 4th Edition, Method 7300.
For ANTIMONY: Refer to NIOSH Manual of Analytical Methods, 2nd Edition, Volume 4, Method P&CAM 261.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Silver white metal with white powder core
Odor: Odorless
Boiling Point: Not Determined
Specific Gravity (H₂O=1): Not Determined
Melting Point: Not Determined
Vapor Pressure (mm Hg): Not Applicable
Vapor Density (Air=1): Not Applicable
Evaporation Rate: Not Applicable
% Solubility In Water: Not Determined
pH: Not Applicable

SECTION 10: STABILITY AND REACTIVITY

Stability: Generally considered stable.

Avoid: None expected.

INCOMPATIBILITY (Materials to Avoid)

Acids, bases, oxidizers, halogens and metal salts.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS

Toxic metal oxides are emitted when heated above the melting point. The amount of fume evolved increases as the temperature rises.

Thermal decomposition may produce ammonia, oxides of carbon and oxides of nitrogen.

Polymerization: Polymerization is not expected to occur.

Avoid: Not applicable.

SECTION 11: TOXICOLOGICAL INFORMATION

CHEMICAL NAME	% Wt.	LD50	LC50
TIN			
CAS NO.: 7440-31-5	93-95	Not Available	Not Available
ANTIMONY			
CAS NO.: 7440-36-0	4-5	7,000 mg/kg RAT, oral	Not Available
UREA			
CAS NO.: 57-13-6	1-2.5	8,471 mg/kg RAT, oral	Not Available
OXYALKYLENE POLYMER			
CAS NO.: 25322-68-3	0.5-1.5	27,500 mg/kg RAT, oral	Not Available

OTHER STUDIES

There is limited evidence that ANTIMONY may decrease female fertility.

NOTE: See Sections 3, 8 and 12 for additional information.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICITY

No data available.

ENVIRONMENTAL FATE

No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

US EPA Waste Number: Not Regulated

Federal, state and local disposal laws and regulations will determine the proper waste disposal/recycling/reclamation procedure. All waste materials should be reviewed to determine the applicable hazards (testing may be necessary). Disposal requirements are dependent on the hazard classification and will vary by location and the type of disposal selected.

****NOTE**** Chemical additions, processing or otherwise altering this material may make the waste management information presented above incomplete, inaccurate or otherwise inappropriate.

As local regulations may vary; all waste must be disposed/recycled/reclaimed in accordance with federal, state, and local environmental control regulations.

SECTION 14: TRANSPORT INFORMATION

INTERNATIONAL

UN Number: Not Regulated

UNITED STATES

EPA Waste Number: Not Regulated
DOT Classification: Not Regulated

CANADA

PIN Number: Not Regulated
TDG Class: Not Regulated

EC

DGL: Not Determined

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

TSCA: IN TSCA

SARA 311 AND 312 HAZARD CATEGORIES

IMMEDIATE (Acute) Health Hazard: YES
DELAYED (Chronic) Health Hazard: YES
FIRE Hazard: NO
REACTIVITY Hazard: NO
Sudden Release of PRESSURE: NO

SARA SECTION 313 NOTIFICATION

This product contains a toxic chemical (or chemicals) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

CHEMICAL NAME	CAS Number	% Wt.
ANTIMONY	7440-36-0	4-5

OZONE DEPLETING SUBSTANCES (ODS)

This product neither contains nor is manufactured with an ozone depleting substance subject to the labeling requirements of the Clean Air Act Amendments 1990 and 40 CFR Part 82.

VOLATILE ORGANIC COMPOUNDS (VOC)

Not Determined

US STATE REGULATIONS

VOLATILE ORGANIC COMPOUND (CARB): Not Determined

CANADIAN REGULATIONS

"This product has been classified in accordance with the hazard criteria of the **Controlled Products Regulations** and the MSDS contains all the information required by the **Controlled Products Regulations**."

DSL/NDSL: DSL

WHMIS Classification: Uncontrolled Product

EUROPEAN REGULATIONS

EINECS: No

OTHER REGULATIONS

MITI (Japan): Yes

AICS (Australia): Yes

SECTION 16: OTHER INFORMATION

REVISIONS

Revision Number: 4

PREPARATION INFORMATION

Prepared By: Wolverine Joining Technologies, and Wolverine Tube Inc.
Corporate Environmental, Health and Safety Group.

Phone Number/Address: See Section 1

This Material Data Sheet is offered pursuant to OSHA's Hazard Communication Standard (29 CFR 1910.1200). Other government regulations must be reviewed for applicability to these products. The information in this Material Safety Data Sheet should be provided to all who will use, handle, store, transport, or otherwise be exposed to this product. This information has been prepared for the guidance of plant engineering, operations, and management and for persons working with or handling these products. The information presented in the MSDS is premised upon proper handling and anticipated uses and is for the material without chemical additions/alterations. We believe this information to be reliable and up-to-date as of the date of publication, but make no warranty that it is. Additionally, if this Material Safety Data Sheet is more than three years old, please contact the supplier at the phone number listed in Section 1 to make certain that this sheet is the most current. Copyright Wolverine Joining Technologies, LLC. License granted to make unlimited copies for internal use only.