



Code: WHITE-FLUX-9  
Date: 04 FEB 1999  
Revised: 1 NOV 2010  
Printed: 1 NOV 2010

WOLVERINE JOINING TECHNOLOGIES, LLC.

MATERIAL SAFETY DATA SHEET

Product: WHITE FLUX 9

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Common Name : BRAZING FLUX  
Chemical Name : CHEMICAL MIXTURE  
Formula : CHEMICAL MIXTURE  
Product CAS No.: CHEMICAL MIXTURE  
Product Use : Welding/Brazing/Soldering

Supplier : WOLVERINE JOINING TECHNOLOGIES, LLC.  
Address : 235 KILVERT STREET  
City, St, Zip : WARWICK, RI 02886  
Phone : 1-401-739-9550

FOR CHEMICAL EMERGENCY CALL CHEMTREC (24 HOURS):  
1-800-424-9300 (US, Canada, Puerto Rico, Virgin Islands)  
1-703-527-3887 (Outside Above Area)

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	CAS NO.	% Wt.
BORIC ACID	10043-35-3	20-40
POTASSIUM SILICOFLUORIDE	16871-90-2	10-30
POTASSIUM FLUOBORATE	14075-53-7	5-20
SODIUM TETRABORATE	1303-96-4	5-20
CALCIUM CARBONATE	1317-65-3	5-20

INGREDIENT NOTES

NOTE: The percentage by weight values reported for the ingredients in this product represent approximate formulation values. See Section 8 for Exposure Limits and Section 11 for Toxicological Information.

### SECTION 3: HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

White paste

Odorless

Flash Point: Not Applicable

Prolonged or repeated exposure may cause liver and kidney damage.  
May cause burns.

May cause eye, skin and respiratory tract irritation.

Harmful if inhaled, swallowed or absorbed through the skin. May cause abdominal pain, nausea, vomiting, diarrhea, tremors, twitching and central nervous system depression, including headache, dizziness and drowsiness.

Long term exposure to fluorides may cause damage to teeth and bones.

Not a fire or explosion hazard. However, toxic and corrosive fluoride compounds may be released in a fire situation.

#### ROUTES OF ENTRY

Eyes? YES

Skin? YES

Inhalation? YES

Ingestion? YES

#### POTENTIAL HEALTH EFFECTS

EYE CONTACT causes irritation and may cause burns.

SKIN CONTACT may cause irritation and possibly fluoride burns which may not be immediately painful or evident, especially on prolonged contact. This material may be absorbed through the skin resulting in systemic poisoning. Symptoms of poisoning are similar to those that occur with ingestion.

INHALATION of dust or fume may cause respiratory tract and mucous membrane irritation. Symptoms include coughing, sore throat and difficulty breathing. Severe exposure may cause pulmonary edema. Absorption may cause systemic poisoning similar to that which occurs with ingestion.

INGESTION may cause irritation and burning of the gastrointestinal tract with abdominal pain, nausea, vomiting and diarrhea. Absorption may cause tremors and twitching as well as central nervous system depression with symptoms of headache, dizziness, weakness, drowsiness and fatigue.

#### CARCINOGENICITY

NTP? NO

IARC? NO

OSHA? NO

#### CHRONIC HEALTH HAZARDS

Prolonged or repeated overexposure may cause kidney and liver damage.

Exposure to FLUORIDES over years may produce mottling of tooth enamel, embrittlement and calcification of bones, and increased calcification of ligaments and vertebrae resulting in spinal stiffness (fluorosis).

Prolonged absorption of BORON COMPOUNDS may cause mild gastrointestinal irritation, loss of appetite, nausea and erythematous rash. Dryness of the skin and mucous membranes, loss of hair, conjunctivitis and kidney injury have also been observed. Reproductive effects have been observed in laboratory animals.

#### MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

May adversely affect existing medical conditions such as eye, skin, respiratory, liver and/or kidney ailments, and central nervous system or cardiovascular disorders.

NOTE: See Section 8 for Exposure Limits, Section 11 for Toxicological Information and Section 12 for Ecological Information.

#### SECTION 4: FIRST AID MEASURES

**EYE CONTACT:** Immediately flush eyes with plenty of water for at least 30 minutes. Hold eyelids open during this flushing with water. Call a physician immediately.

**SKIN CONTACT:** Flush area with water while removing contaminated clothing and shoes. Follow by washing with soap and large amounts of water until no evidence of chemical remains (15-20 minutes). For burns, cover with a sterile, dry, loose-fitting dressing. Get medical attention.

**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician.

**INGESTION:** If swallowed, "DO NOT INDUCE VOMITING", give 3-4 glasses of water. Do not give anything by mouth to an unconscious or convulsing person. Get immediate medical attention.

#### SECTION 5: FIRE-FIGHTING MEASURES

Flash Point: Not Applicable  
Auto-Ignition: Not Applicable  
LEL: Not Applicable  
UEL: Not Applicable  
NFPA HAZARD CLASSIFICATION

Health: 3                      Flammable: 0                      Reactivity: 0

HMIS HAZARD CLASSIFICATION

Health: 3\*                      Flammable: 0                      Reactivity: 0                      Special: D

\* Indicates the possibility of chronic health effects. See Chronic Health Hazards in Section 3 for more information.

#### EXTINGUISHING MEDIA

Use extinguishing media appropriate for surrounding fire.

#### SPECIAL FIRE FIGHTING PROCEDURES

Wear NIOSH/MSHA approved positive-pressure self-contained breathing apparatus and protective clothing as specified in 29 CFR 1910.156.

#### UNUSUAL FIRE AND EXPLOSION HAZARDS

Not a fire or explosion hazard. However, toxic and corrosive fluoride compounds may be released in a fire situation.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

Contain spillage and scoop up or vacuum. Notification of the National Response Center (800/424-8802) may be required. Refer to EPA, DOT and applicable state and local regulations for current response information.

It is recommended that each user establish a spill prevention, control and countermeasure plan (SPCC). Such plan should include procedures applicable to proper storage, control and clean-up of spills, including reuse or disposal as appropriate (see Section 13: Disposal Considerations).

**\*\*NOTE\*\*** In the event of an accidental release of this material, the above procedures should be followed. Additionally, proper exposure controls and personal protection equipment should be used (see Section 8: Exposure Control/Personal Protection), and disposal of the material should be in accordance with Section 13: Disposal Considerations.

### SECTION 7: HANDLING AND STORAGE

Wash thoroughly after handling.

Keep container closed.

Store in a cool, dry location away from incompatible materials.

Avoid contact with any dusts, mists or fumes resulting from the use of this product.

Do not eat, drink, or smoke in work area.

Use with adequate ventilation.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### EXPOSURE LIMITS

##### INGREDIENT

##### PEL-OSHA

##### TLV-ACGIH

##### BORIC ACID

CAS NO.: 10043-35-3

None Established

None Established

POTASSIUM SILICOFLUORIDE CAS NO.: 16871-90-2	2.5 mg/m3 (as F)	2.5 mg/m3 (as F)
POTASSIUM FLUOBORATE CAS NO.: 14075-53-7	2.5 mg/m3 (as F)	2.5 mg/m3 (as F)
SODIUM TETRABORATE CAS NO.: 1303-96-4	None Established	5 mg/m3
CALCIUM CARBONATE CAS NO.: 1317-65-3	15 mg/m3 (Total dust) 5 mg/m3 (Respirable dust)	10 mg/m3

NOTE: Both OSHA and the ACGIH list welding fumes as having an exposure limit of 5 mg/m3 (total particulate not otherwise classified). However, the ACGIH states that welding fumes must be tested frequently for individual components which are likely to be present to determine whether specific exposure limits are exceeded. Unless otherwise noted, all values are reported as 8-hour Time-Weighted Averages (TWAs) and total dust (particulates only). All ACGIH TLVs refer to the 1998 Standards. All OSHA PELs refer to 29 CFR Part 1910 Air Contaminants: Final Rule, January 19, 1989.

#### RESPIRATORY PROTECTION

If there is a potential to exceed the TLV, NIOSH/MSHA approved respiratory protection is required. For airborne levels up to 10 times the appropriate TLV's, an air purifying acid gas cartridge respirator would be suitable. If used in a manner that generates a mist, a dust/mist cartridge as well as the acid gas cartridge would be necessary. Above 10 times the TLV, an air supplied full facepiece respirator would be required. If respiratory protection is used, follow all the requirements for respirator programs set forth in the OSHA regulations (29 CFR 1910.139).

#### VENTILATION

General; local exhaust ventilation as necessary to control any air contaminants to within their PELs or TLVs during the use of this product.

#### PROTECTIVE EQUIPMENT

Chemical goggles.  
Rubber or neoprene gloves.  
Body protection as necessary to prevent skin contact.  
Refer to ANSI/ASC Z49.1-94 (Safety in Welding, Cutting and Allied Processes), published by the American Welding Society, for further information on the selection of personal protective equipment.

#### PERSONNEL SAMPLING PROCEDURE

For FLUORIDE COMPOUNDS: Refer to NIOSH Manual of Analytical Methods (NMAM), 4th Edition, Methods 7902, 7906.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: White paste  
Odor: Odorless  
Boiling Point: Not Determined  
Specific Gravity (H2O=1): Not Determined  
Melting Point: Not Determined  
Vapor Pressure (mm Hg): Not Applicable  
Vapor Density (Air=1): Not Applicable  
Evaporation Rate: Not Applicable  
% Solubility In Water: Not Determined  
pH: Not Determined

SECTION 10: STABILITY AND REACTIVITY

Stability: Generally considered stable.  
Avoid: Temperatures above 500°C.

INCOMPATIBILITY (Materials to Avoid)

Acids, bases, strong oxidizers, reducing agents, combustibles.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS

Emits toxic and corrosive fluoride compounds. May also emit oxides of boron and potassium when heated to decomposition.

Polymerization: Polymerization is not expected to occur.  
Avoid: Not applicable.

SECTION 11: TOXICOLOGICAL INFORMATION

CHEMICAL NAME	% Wt.	LD50	LC50
BORIC ACID CAS NO.: 10043-35-3	20-40	3,450 mg/kg MOUSE, oral	9,600 ug/m <sup>3</sup> /4 hr RAT
POTASSIUM SILICOFLUORIDE CAS NO.: 16871-90-2	10-30	156 mg/kg RAT, oral	Not Available
POTASSIUM FLUOBORATE CAS NO.: 14075-53-7	5-20	Not Available	Not Available
SODIUM TETRABORATE CAS NO.: 1303-96-4	5-20	2,660 mg/kg RAT, oral	Not Available
CALCIUM CARBONATE CAS NO.: 1317-65-3	5-20	> 5000 mg/kg UNSPECIFIED	Not Available

NOTE: See Sections 3, 8 and 12 for additional information.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICITY

No data available.

ENVIRONMENTAL FATE

No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

US EPA Waste Number: Not Regulated

Federal, state and local disposal laws and regulations will determine the proper waste disposal/recycling/reclamation procedure. All waste materials should be reviewed to determine the applicable hazards (testing may be necessary). Disposal requirements are dependent on the hazard classification and will vary by location and the type of disposal selected.

**\*\*NOTE\*\*** Chemical additions, processing or otherwise altering this material may make the waste management information presented above incomplete, inaccurate or otherwise inappropriate.

As local regulations may vary; all waste must be disposed/recycled/reclaimed in accordance with federal, state, and local environmental control regulations.

SECTION 14: TRANSPORT INFORMATION

INTERNATIONAL

UN Number: UN3287

UNITED STATES

EPA Waste Number: Not Regulated

DOT Classification: 6.1 Poisonous materials

DOT Proper Shipping Name: Toxic liquid, inorganic, n.o.s. (Contains Potassium Silicofluoride)

Packing Group: III

CANADA

PIN Number: UN3287

TDG Class: 6.1 Poisonous materials

EC

DGL: Toxic substance

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

TSCA: IN TSCA

SARA 311 AND 312 HAZARD CATEGORIES

IMMEDIATE (Acute) Health Hazard: YES  
DELAYED (Chronic) Health Hazard: YES  
FIRE Hazard: NO  
REACTIVITY Hazard: NO  
Sudden Release of PRESSURE: NO

SARA SECTION 313 NOTIFICATION

This product does not contain toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

OZONE DEPLETING SUBSTANCES (ODS)

This product neither contains nor is manufactured with an ozone depleting substance subject to the labelling requirements of the Clean Air Act Amendments 1990 and 40 CFR Part 82.

VOLATILE ORGANIC COMPOUNDS (VOC)

Not Determined

US STATE REGULATIONS

VOLATILE ORGANIC COMPOUND (CARB): Not Determined

CANADIAN REGULATIONS

"This product has been classified in accordance with the hazard criteria of the *Controlled Products Regulations* and the MSDS contains all the information required by the *Controlled Products Regulations*."

DSL/NDSL: DSL

WHMIS Classification: Class D Division 2 Subdivision B

EUROPEAN REGULATIONS

EINECS: Yes

OTHER REGULATIONS

MITI (Japan): No

AICS (Australia): Yes

SECTION 16: OTHER INFORMATION

REVISIONS

Revision Number: 5

PREPARATION INFORMATION

Prepared By: Wolverine Joining Technologies, and Wolverine Tube Inc.  
Corporate Environmental, Health and Safety Group.

Phone Number/Address: See Section 1

---

This Material Data Sheet is offered pursuant to OSHA's Hazard Communication Standard (29 CFR 1910.1200). Other government regulations must be reviewed for applicability to these products. The information in this Material Safety Data Sheet should be provided to all who will use, handle, store, transport, or otherwise be exposed to this product. This information has been prepared for the guidance of plant engineering, operations, and management and for persons working with or handling these products. The information presented in the MSDS is premised upon proper handling and anticipated uses and is for the material without chemical additions/alterations. We believe this information to be reliable and up-to-date as of the date of publication, but make no warranty that it is. Additionally, if this Material Safety Data Sheet is more than three years old, please contact the supplier at the phone number listed in Section 1 to make certain that this sheet is the most current. Copyright Wolverine Joining Technologies, LLC. License granted to make unlimited copies for internal use only.